



Winkelschwenkverschraubungen - mit Außensechskant

Messing vernickelt, technische Daten und Erklärungen auf Seite A2

| Bestell-Nr. | Schlauch Ø D | Gewinde G | ØC | ØB | H | L | ↙ | | Euro |
|-------------|-----------------|--------------|----|------|------|------|----|--|------|
| 017-5-4 | 4 | M5 | 7 | 4,5 | 17,5 | 18,5 | 8 | | 1,67 |
| 017-5-5 | 5 | M5 | 7 | 4,5 | 17,5 | 19,5 | 8 | | 1,77 |
| 017-18-4 | 4 | G1/8 | 14 | 7,5 | 28,0 | 21,0 | 14 | | 1,77 |
| 017-18-5 | 5 | G1/8 | 14 | 7,5 | 28,0 | 22,5 | 14 | | 1,77 |
| 017-18-6 | 6 | G1/8 | 14 | 7,5 | 28,0 | 22,5 | 14 | | 1,77 |
| 017-18-8 | 8 | G1/8 | 14 | 7,5 | 28,0 | 24,5 | 14 | | 2,02 |
| 017-14-6 | 6 | G1/4 | 18 | 9,0 | 33,0 | 24,0 | 17 | | 2,12 |
| 017-14-8 | 8 | G1/4 | 18 | 9,0 | 33,0 | 26,0 | 17 | | 2,22 |
| 017-14-10 | 10 | G1/4 | 18 | 9,0 | 33,0 | 27,0 | 17 | | 2,80 |
| 017-38-8 | 8 | G3/8 | 21 | 10,0 | 37,0 | 28,0 | 22 | | 2,92 |
| 017-38-10 | 10 | G3/8 | 21 | 10,0 | 37,0 | 29,0 | 22 | | 3,17 |
| 017-38-12 | 12 | G3/8 | 21 | 10,0 | 37,0 | 30,0 | 22 | | 3,47 |

Winkelschwenkverschraubungen - mit Außensechskant

- vernickelter Lösering, technische Daten und Erklärungen auf Seite A2

| Bestell-Nr. | Schlauch Ø D | Gewinde G | ØC | ØB | H | L | ↙ | | Euro |
|-------------|-----------------|--------------|----|------|------|------|----|--|------|
| 017-5-4Ni | 4 | M5 | 7 | 4,5 | 17,5 | 18,5 | 8 | | 1,73 |
| 017-5-5Ni | 5 | M5 | 7 | 4,5 | 17,5 | 19,5 | 8 | | 1,83 |
| 017-18-4Ni | 4 | G1/8 | 14 | 7,5 | 28,0 | 21,0 | 14 | | 1,83 |
| 017-18-5Ni | 5 | G1/8 | 14 | 7,5 | 28,0 | 22,5 | 14 | | 1,83 |
| 017-18-6Ni | 6 | G1/8 | 14 | 7,5 | 28,0 | 22,5 | 14 | | 1,83 |
| 017-18-8Ni | 8 | G1/8 | 14 | 7,5 | 28,0 | 24,5 | 14 | | 2,09 |
| 017-14-6Ni | 6 | G1/4 | 18 | 9,0 | 33,0 | 24,0 | 17 | | 2,20 |
| 017-14-8Ni | 8 | G1/4 | 18 | 9,0 | 33,0 | 26,0 | 17 | | 2,28 |
| 017-14-10Ni | 10 | G1/4 | 18 | 9,0 | 33,0 | 27,0 | 17 | | 2,92 |
| 017-38-8Ni | 8 | G3/8 | 21 | 10,0 | 37,0 | 28,0 | 22 | | 3,00 |
| 017-38-10Ni | 10 | G3/8 | 21 | 10,0 | 37,0 | 29,0 | 22 | | 3,27 |
| 017-38-12Ni | 12 | G3/8 | 21 | 10,0 | 37,0 | 30,0 | 22 | | 3,59 |

T-Schwenkverschraubungen - mit Außensechskant

Messing vernickelt, technische Daten und Erklärungen auf Seite A2

| Bestell-Nr. | Schlauch Ø D | Gewinde G | ØB | H | L1 | L | ↙ | | Euro |
|-------------|-----------------|--------------|----|------|------|------|----|--|------|
| 018-5-4 | 4 | M5 | 7 | 4,5 | 17,5 | 18,5 | 8 | | 2,68 |
| 018-5-5 | 5 | M5 | 7 | 4,5 | 17,5 | 19,5 | 8 | | 2,73 |
| 018-18-4 | 4 | G1/8 | 14 | 7,5 | 28,0 | 21,0 | 14 | | 2,87 |
| 018-18-5 | 5 | G1/8 | 14 | 7,5 | 28,0 | 22,5 | 14 | | 2,87 |
| 018-18-6 | 6 | G1/8 | 14 | 7,5 | 28,0 | 22,5 | 14 | | 2,73 |
| 018-18-8 | 8 | G1/8 | 14 | 7,5 | 28,0 | 24,5 | 14 | | 2,79 |
| 018-14-6 | 6 | G1/4 | 18 | 9,0 | 33,0 | 24,0 | 17 | | 3,02 |
| 018-14-8 | 8 | G1/4 | 18 | 9,0 | 33,0 | 26,0 | 17 | | 3,17 |
| 018-14-10 | 10 | G1/4 | 18 | 9,0 | 33,0 | 27,0 | 17 | | 3,92 |
| 018-38-8 | 8 | G3/8 | 21 | 10,0 | 37,0 | 28,0 | 22 | | 3,84 |
| 018-38-10 | 10 | G3/8 | 21 | 10,0 | 37,0 | 29,0 | 22 | | 4,03 |
| 018-38-12 | 12 | G3/8 | 21 | 10,0 | 37,0 | 30,0 | 22 | | 5,38 |