

## Winkelschraubverschraubungen schwenkbar - mit Innensechskant

- vernickelter Lösering, technische Daten und Erklärungen auf Seite A2

| Bestell-Nr. | Schlauch<br>Ø D | Gewinde<br>G | Ø A  | H | L 1  | L    | ○ | Euro |
|-------------|-----------------|--------------|------|---|------|------|---|------|
| 015-5-4Ni   | 4               | M5           | 2,0  | 4 | 17,0 | 18,5 | 2 | 2,20 |
| 015-5-5Ni   | 5               | M5           | 2,0  | 4 | 17,0 | 19,5 | 2 | 2,20 |
| 015-18-4Ni  | 4               | G1/8         | 5,5  | 6 | 25,0 | 21,0 | 3 | 2,32 |
| 015-18-5Ni  | 5               | G1/8         | 5,5  | 6 | 25,0 | 22,5 | 3 | 2,32 |
| 015-18-6Ni  | 6               | G1/8         | 5,5  | 6 | 25,0 | 23,5 | 3 | 2,20 |
| 015-18-8Ni  | 8               | G1/8         | 5,5  | 6 | 25,0 | 24,5 | 3 | 2,20 |
| 015-14-6Ni  | 6               | G1/4         | 7,8  | 8 | 29,3 | 24,5 | 4 | 2,84 |
| 015-14-8Ni  | 8               | G1/4         | 7,8  | 8 | 29,3 | 26,0 | 4 | 2,84 |
| 015-14-10Ni | 10              | G1/4         | 7,8  | 8 | 29,3 | 27,0 | 4 | 2,94 |
| 015-38-8Ni  | 8               | G3/8         | 10,0 | 9 | 34,0 | 29,0 | 5 | 3,17 |
| 015-38-10Ni | 10              | G3/8         | 10,0 | 9 | 34,0 | 29,0 | 5 | 3,17 |
| 015-38-12Ni | 12              | G3/8         | 10,0 | 9 | 34,0 | 29,0 | 5 | 3,92 |

## T-Einschraubverschraubungen schwenkbar - mit Innensechskant

Messing vernickelt, technische Daten und Erklärungen auf Seite A2

| Bestell-Nr. | Schlauch<br>Ø D | Gewinde<br>G | Ø A  | H | L 1  | L    | ○ | Euro |
|-------------|-----------------|--------------|------|---|------|------|---|------|
| 016-5-4     | 4               | M5           | 2,0  | 4 | 17,0 | 18,5 | 2 | 2,66 |
| 016-5-5     | 5               | M5           | 2,0  | 4 | 17,0 | 19,5 | 2 | 2,66 |
| 016-18-4    | 4               | G1/8         | 5,5  | 6 | 25,0 | 21,0 | 3 | 2,84 |
| 016-18-5    | 5               | G1/8         | 5,5  | 6 | 25,0 | 22,5 | 3 | 2,84 |
| 016-18-6    | 6               | G1/8         | 5,5  | 6 | 25,0 | 23,5 | 3 | 3,07 |
| 016-18-8    | 8               | G1/8         | 5,5  | 6 | 25,0 | 24,5 | 3 | 3,07 |
| 016-14-6    | 6               | G1/4         | 7,8  | 8 | 29,3 | 24,5 | 4 | 3,28 |
| 016-14-8    | 8               | G1/4         | 7,8  | 8 | 29,3 | 26,0 | 4 | 3,38 |
| 016-14-10   | 10              | G1/4         | 7,8  | 8 | 29,3 | 27,0 | 4 | 3,62 |
| 016-38-8    | 8               | G3/8         | 10,0 | 9 | 34,0 | 29,0 | 5 | 3,98 |
| 016-38-10   | 10              | G3/8         | 10,0 | 9 | 34,0 | 29,0 | 5 | 3,98 |
| 016-38-12   | 12              | G3/8         | 10,0 | 9 | 34,0 | 29,0 | 5 | 5,09 |

## T-Einschraubverschraubungen schwenkbar - mit Innensechskant

- vernickelter Lösering, Messing vernickelt, technische Daten und Erklärungen auf Seite A2

| Bestell-Nr. | Schlauch<br>Ø D | Gewinde<br>G | Ø A  | H | L 1  | L    | ○ | Euro |
|-------------|-----------------|--------------|------|---|------|------|---|------|
| 016-5-4Ni   | 4               | M5           | 2,0  | 4 | 17,0 | 18,5 | 2 | 2,84 |
| 016-5-5Ni   | 5               | M5           | 2,0  | 4 | 17,0 | 19,5 | 2 | 2,84 |
| 016-18-4Ni  | 4               | G1/8         | 5,5  | 6 | 25,0 | 21,0 | 3 | 2,84 |
| 016-18-5Ni  | 5               | G1/8         | 5,5  | 6 | 25,0 | 22,5 | 3 | 2,84 |
| 016-18-6Ni  | 6               | G1/8         | 5,5  | 6 | 25,0 | 23,5 | 3 | 3,28 |
| 016-18-8Ni  | 8               | G1/8         | 5,5  | 6 | 25,0 | 24,5 | 3 | 3,28 |
| 016-14-6Ni  | 6               | G1/4         | 7,8  | 8 | 29,3 | 24,5 | 4 | 3,49 |
| 016-14-8Ni  | 8               | G1/4         | 7,8  | 8 | 29,3 | 26,0 | 4 | 3,49 |
| 016-14-10Ni | 10              | G1/4         | 7,8  | 8 | 29,3 | 27,0 | 4 | 3,87 |
| 016-38-8Ni  | 8               | G3/8         | 10,0 | 9 | 34,0 | 29,0 | 5 | 4,25 |
| 016-38-10Ni | 10              | G3/8         | 10,0 | 9 | 34,0 | 29,0 | 5 | 4,25 |
| 016-38-12Ni | 12              | G3/8         | 10,0 | 9 | 34,0 | 29,0 | 5 | 5,44 |

